



750 – 1000 cfm

Portable Air Compressors



Of all the things you worry about on the jobsite, this compressor won't be among them. Set it up, perform regular maintenance, and forget about it. After all, it's made by Ingersoll Rand.

Uncompromising performance, compact design

Ingersoll Rand offers the widest range of compressors, backed with years of expertise and designed to tackle all your applications. Ingersoll Rand compressors assure complete satisfaction, from ease of service access, to simple user controls, to rugged reliability. The cool-box design keeps the internal components cool to prolong life, and the single-wall coolers allow quick and easy maintenance. Integrated electronics alert customers of issues that may reduce productivity. A full galvanneal enclosure comes standard for maximum corrosion protection and reliability. The Ingersoll Rand world wide service and support network will be with you during every stage of the compressor's lifecycle.

MODEL		VHP750WCAT	MHP825WCU	HP915WCU	XP1000WCU	PERFORMANCE FEATURES	
COMPRESSOR — ROTARY SCREW / SINGLE-STAGE 2-STAGE							
Free-air Delivery – cfm (m ³ /min)		750 (23.4)	825 (23.4)	915 (25.9)	1,000 (28.3)	<ul style="list-style-type: none"> Compact size increases maneuverability Galvanneal sheet metal enclosure for ultimate corrosion protection High-speed running gear is standard Large fuel tank lasts the full shift Microprocessor-controlled engine panel increases efficiency; backlit gauges include engine temperature, hour meter, volt meter, discharge air temperature, engine oil pressure, tachometer, and fuel level Rear steps allow easier access to radiator for refilling engine coolant 	
Rated Operating Pressure – psig (bar)		200 (13.8)	175 (12.1)	150 (10.3)	125 (8.6)		
Pressure Range – psig (bar)		80 – 225 (5.5 – 15.5)	80 – 200 (5.5 – 13.8)	80 – 175 (5.5 – 12.1)	80 – 150 (5.5 – 10.3)		
Air Discharge Outlet Size – in (mm)		2 (50.8)	2 (50.8)	2 (50.8)	2 (50.8)		
Air Discharge Outlet Quantity		1	1	1	1		
ENGINE — TIER 3 / STAGE III							
Make		Caterpillar	Cummins	Cummins	Cummins	AVAILABLE OPTIONS (FACTORY-INSTALLED) <ul style="list-style-type: none"> Aftercooler with water separator Central drains Cold-start kit includes engine block heaters, engine oil pan, batteries Dual pressure regulation Hydraulic surge breakers IQ System™ aftercooler plus particulate with patented disposal system Wagon or less running gear options 	
Model		C-9	QSL-9	QSL-9	QSL-9		
Number Of Cylinders		6	6	6	6		
Displacement – cu in (L)		535 (8.8)	543 (8.9)	543 (8.9)	543 (8.9)		
Rated Speed – rpm		1,800	1,800	1,800	1,800		
Idle Speed – rpm		1,200	1,200	1,200	1,200		
Bhp (kW) @ Rated Speed		300 (220)	300 (220)	300 (220)	300 (220)		
Electrical		24 V	24 V	24 V	24 V		
DIMENSIONS W/ RUNNING GEAR							
Length – in (mm)	Wagon	166 (4210)	166 (4210)	166 (4210)	166 (4210)		
	High Speed	215 (5461)	215 (5461)	215 (5461)	215 (5461)		
Width – in (mm)	Wagon	79 (2007)	79 (2007)	79 (2007)	79 (2007)		
	High Speed	79 (2007)	79 (2007)	79 (2007)	79 (2007)		
Height – in (mm)	Wagon	91.2 (2316)	91.2 (2316)	91.2 (2316)	91.2 (2316)		
	High Speed	92.7 (2355)	92.7 (2355)	92.7 (2355)	92.7 (2355)		
Track Width – in (mm)	Wagon	66.3 (1684)	66.3 (1684)	66.3 (1684)	66.3 (1684)		
	High Speed	68.4 (1737)	68.4 (1737)	68.4 (1737)	68.4 (1737)		
Tire Size – in (mm)	Wagon	16 (406)	16 (406)	16 (406)	16 (406)		
	High Speed	14.5 (368)	14.5 (368)	14.5 (368)	14.5 (368)		
Shipping Weight — No Fuel – lb (kg)	Wagon	9,570 (4350)	9,370 (4259)	9,370 (4259)	9,370 (4259)		
	High Speed	9,680 (4400)	9,480 (4300)	9,480 (4300)	9,480 (4300)		
Working Weight — w/ Fuel – lb (kg)	Wagon	10,550 (4795)	10,350 (4705)	10,350 (4705)	10,350 (4705)		
	High Speed	10,450 (4750)	10,250 (4659)	10,250 (4659)	10,250 (4659)		
Fuel Tank Capacity – gal (L)	Wagon	140 (530)	140 (530)	140 (530)	140 (530)		
	High Speed	110 (515)	110 (515)	110 (515)	110 (515)		
DIMENSIONS W/O RUNNING GEAR							
Length – in (mm)		153 (3886)	153 (3886)	153 (3886)	153 (3886)		
Add 8" For Service Valve							
Width – in (mm)		79 (2007)	79 (2007)	79 (2007)	79 (2007)		
Height w/ Shock Mounts – in (mm)		77 (1956)	77 (1956)	77 (1956)	77 (1956)		
Shipping Weight — No Fuel – lb (kg)		9,120 (4145)	8,920 (4046)	8,920 (4046)	8,920 (4046)		
Working Weight — w/ Fuel – lb (kg)		10,100 (4591)	9,900 (4500)	9,900 (4500)	9,900 (4500)		



Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

Ingersoll Rand air compressors are not designed, intended, or approved for breathing air. Compressed air should not be used for breathing air applications under any circumstances.

Nothing contained in this brochure is intended to extend any warranty or representation, expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale shall be in accordance with standard Ingersoll Rand terms and conditions of sale for such products, which are available upon request.



(877) IR BRAND • ingersollrand.com